APPLICANT(S): ELATA, David et al.

SERIAL NO.:

10/562,463

FILED:

February 19, 2008

Page 2

AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or

disclaimer to resubmission in a divisional or continuation application claims indicated as

cancelled:

The following listing of claims replaces all versions, and listings, of claims in this

application.

Listing of Claims:

1. (Currently Amended) A device for inducing motion of fluids or solids, the device

comprising: a circular structure with a deformable circular sheet compressed to form a

continuous structural axially symmetric wave that is symmetric about an axis of circular

symmetry of the sheet; and an actuator for actuating the deformable circular sheet and driving

the structural wave in a predetermined manner and in a direction about the sheet axis of

circular symmetry.

2-4. (Canceled)

(Original) The device of claim 1, wherein a first wall is provided against the 5.

deformable sheet so as to define a first conduit between the first wall and the deformable

sheet.

6. (Original) The device of claim 5, wherein the first conduit is provided with an inlet

and an outlet.

7. (Original) The device of claim 5, further provided with a second wall positioned

opposite the first wall, with the deformable sheet between the walls, the second wall defining

a second conduit between the second wall and the deformable sheet.

8. (Original) The device of claim 7, wherein the second conduit is provided with an inlet

and an outlet.

APPLICANT(S): ELATA, David et al.

SERIAL NO.:

10/562,463

FILED:

February 19, 2008

Page 3

9. (Original) The device of claim 1, wherein the actuator is selected from the group

consisting of electrostatic actuators, piezoelectric actuators, thermoelastic actuators and

magnetic actuators.

10. (Previously presented) The device of claim 1, wherein at least a part of the device is

made from silicon.

11. (Currently Amended) A method for inducing motion of fluids or solids, the method

comprising: providing a structure with a deformable circular sheet formed to present a

continuous structural axially symmetric wave that is symmetric about an axis of circular

symmetry of the sheet; and using an actuator to displace the structural wave about the sheet

axis of circular symmetry, thereby imparting displacing forces on an adjacent fluid or solid so

as to displace said adjacent fluid or solid about the sheet axis of circular symmetry.

12. (Original) The method of claim 11, wherein the actuator is operated to continuously

displace the structural waves.

13-15. (Canceled)

16. (Original) The method of claim 11, further comprising providing a first wall against

the deformable sheet so as to define a first conduit between the first wall and the deformable

sheet.

17. (Original) The method of claim 16, further comprising providing the first conduit with

an inlet and an outlet.

18. (Original) The method of claim 16, further comprising providing a second wall

positioned opposite the first wall, with the deformable sheet between the walls, the second

wall defining a second conduit between the second wall and the deformable sheet.

APPLICANT(S): ELATA, David et al.

SERIAL NO.:

10/562,463

FILED:

February 19, 2008

Page 4

19. (Original) The method of claim 18, further comprising providing the second conduit with an inlet and an outlet.

20. (Original) The method of claim 11, wherein actuation of the deformable sheet is selected from the group consisting of electrostatic actuation, piezoelectric actuation, thermoelastic actuation and magnetic actuation.

21-22. (canceled)